

# Xenon Lamp Spectrophotometers

## LXLS-A1 Series



# Xenon Lamp Spectrophotometers LXLS-A1 Series

Xenon Lamp Spectrophotometer LXLS-A1 series consist of a high quality 150 W Xenon light source which offers a wave range of 190 nm to 1100 nm. Photoelectric multiplier tube detectors associated with it provides sufficient light intensity signal to detect sensitivity of a high resolution and this can be detected / adjusted using 7 inch TFT and 10.1 inch TFT coloured capacitive touch screen. This device portrays different work mode; such as T, A, C, E which makes it more flexible to use.

## Features

- Work mode consist of T, A, C, E
- High quality flashing Xenon lamp can be directly used for testing without preheating and its shelf life is for 3 years
- Possess strong functions like photometric measurement, quantitative measurement, kinetics, spectrum scan, DNA/protein test, Multi-wavelength test
- Colossal in built memory is capable of saving up to 1024MB for test data and working curves
- Data transfer can be done via using USB port that easily helps in passing on the data to excel for further processing, analysis and storage
- Large sample chamber easily allows attachment of optional accessories
- Flexible enough to allow USB and SD card storage

## Application

Designed to meet high requirement for précised measurement in the research and produc - tion of organic chemistry, biochemistry, medical testing, food testing, environmental protection, water testing industry, etc.

## Specifications

Model No.	LXLS-A10	LXLS-A11
Optical system	Double Beam, Grating 1200 lines/mm	
Wavelength Range	190 nm to 1100 nm	
Spectral Bandwidth	2 nm	1 nm
Wavelength Accuracy	0.1 nm @ 656.1 nm, 0.3 nm @ all	
Wavelength Repeatability	0.1 nm	
Photometric Accuracy	0.2 % T (0 to 100%T), 0.002 A (0-0.5A), 0.004A(0.5-1A)	
Photometric Repeatability	0.15 % T ( 0-100 % T), 0.001A (0-0.5A), 0.002A(0.5-1A)	
Photometric Range	0-200% T, -0.3 to 3A, 0-9999 C (0-9999 F)	
Stray Light	0.03 % T @ 22 nm, 360 nm	
Stability	0.0005 A/h @500 nm	
Baseline Flatness	0.002 A	0.001 A
Noise	0.0005 A @ 500 nm	
Work Mode	T, A, C, E	
Scanning Speed	High, Medium, Low ( Max 3000 nm/ min )	
Wavelength Setting	Auto	
Display	7 inch TFT Coloured Capacitive Touch Screen	
Light Source	Imported Xenon Lamp	
Detector	Imported Silicon Photodiode	
Cuvette Holder	10 mm single hole cell holder	
Output	USB Drive, USB host, RS232	
Power	AC 220 V/ 500 Hz or AC 110 V / 60 Hz	
Packaging dimension	810 660 390 mm	
Gross Weight	27 kg	

## Specifications

Model No.	LXLS-A13	LXLS-A14	LXLS-A15
Optical system	Double Beam, Grating 1200 lines/mm		
Wavelength Range	190 nm to 1100 nm		
Spectral Bandwidth	2 nm	1 nm	0.5/1/2/4/5 nm
Wavelength Accuracy	0.1 nm @ 656.1 nm, 0.3 nm @ all		
Wavelength Repeatability	0.1 nm		
Photometric Accuracy	0.2 % T (0 to 100%T), 0.002 A (0-0.5A), 0.004A(0.5-1A)		
Photometric Repeatability	0.15 % T ( 0-100 % T), 0.001A (0-0.5A), 0.002A(0.5-1A)		
Photometric Range	0-200% T, -0.3 to 3A, 0-9999 C (0-9999 F)		
Stray Light	0.03 % T @ 22 nm, 360 nm		
Stability	0.0003 A/h @500 nm		
Baseline Flatness	0.002 A	0.001 A	
Noise	0.0005 A @ 500 nm		
Work Mode	T, A, C, E		
Scanning Speed	High, Medium, Low ( Max 3000 nm/ min )		
Wavelength Setting	Auto		
Display	10.1inch TFT Coloured Capacitive Touch Screen		
Light Source	Imported Xenon Lamp		
Detector	Imported Silicon Photodiode		
Cuvette Holder	10 mm single hole cell holder		
Output	USB Drive, USB host, RS232		
Power	AC 220 V/ 500 Hz or AC 110 V / 60 Hz		
Packaging dimension	810 660 390 mm		810 690 520 mm
Gross Weight	27 kg		45 kg

## Standard Accessories

Sr. No.	Accessory	Quantity
1.	10 mm glass cuvette	4
2.	10 mm quartz cuvette	2
3.	Power cord	
4.	PC Software	

## Optional Accessories

Sr. No.	Accessory	Quantity
1.	Peltier / Sipper system	1 pc per box
2.	Reflection accessories	
3.	21 CRF compliant software	1 pc per box
4.	5 mm Glass Cuvettes	4 pcs per box
5.	20 mm Glass Cuvettes	2 pcs per box
6.	5 mm Quartz Cuvettes	2 pcs per box
7.	20 mm Quartz Cuvettes	2 pcs per box
8.	10 50 mm Manual 4-cell holder	1 pc per box
9.	100 mm Manual 4-cell holder	1 pc per box
10.	Auto 8-position cell holder	1 pc per box
11.	Solid holder / Film holder	1 pc per box
12.	Thermal Printer	1 pc per box