

# Multifunctional Ultrasonic Cleaner

LMFU-A10

#### Multifunctional Ultrasonic Cleaner LMFU-A10

Multifunctional Ultrasonic Cleaner LMFU-A10 is a single 6.5 L multifunctional tank with heat and ultrasonic action providing deep cleansing, removing contamination even from blind holes and internal surfaces. Its multifunctionality includes power adjusting mode, pulse or degas control and variable ultrasonic intensity control. Equipped with degassing and degreasing function for removal of dissolved gasses and cleansing of the tank.

#### **Features**

- ♦ 6.5 L capacity tank
- Integrated digital circuit for timer and heater
- Temperature range : 0 °C ~ 100 °C
- Power adjustable mode
- Cleaning duration: 1 ~ 99 mins (can be kept 'ON' always)
- 4 working modes available (Power, Pulse, Turbo, Degas)
- One key access for auto stand-by, sleep and wake up mode
- On power cut, auto memory save option
- Efficient cleaning by distilled water
- Equipped with degassing and degreasing function
- Precise digital processed temperature controls
- Optimum durability under prolonged and heavy usage

#### **Application**

Ideal for cleaning irregular and complex instruments, lenses and other optical parts, dental and surgical instruments, electronics. It is also used in extraction and to degas certain analyzed stuff in laboratories

### Multifunctional Ultrasonic Cleaner LMFU-A10

## **Specifications**

| Model No.                  | LMFU - A10                           |
|----------------------------|--------------------------------------|
| Capacity                   | 6.5 L                                |
| Tank size ( L x W x H )    | 300 x 155 x 150 mm                   |
| Overall size ( L x W x H ) | 330 x 180 x 357 mm                   |
| Ultrasonic power           | O ~ 180 W                            |
| Heater power               | 300 W                                |
| Temperature set            | 0 °C ~ 100 °C                        |
| Timer                      | 1 ~ 99 mins ( optional : always ON ) |
| Construction material      | Stainless Steel                      |
| Drainage                   | Yes                                  |
| Voltage                    | AC 220 V / 50 Hz                     |