



AUTOMATIC POLARIMETER

LPMR-A30

AUTOMATIC POLARIMETER LPMR-A30

The automatic polarimeter LPMR-A30 comes with 7 inch TFT touch screen & long-life LED with 589 nm filter as light source instead of traditional limited hours light source for use. With four measurement options like optical rotation, specific rotation, concentration and international sugar content it can determine the concentration of substance, content, purity etc. Equipped with built-in peltier temperature control system ensures accurate readings. Polarimeter is used across sugar, pharmacy, food & chemistry industry.

Features

- ◆ Highly integrated, fully automatic Polarimeter
- ◆ 7 inch TFT touch screen
- ◆ 4 selectable measurement options
- ◆ Long LED life light source, with 589.3 nm filter
- ◆ Built-in Parr (peltier) temperature control system
- ◆ $\pm 89^\circ$ measurement scope for chiral compounds over broad range of concentration
- ◆ Automatic calculations of non-standard test tube measurements
- ◆ Automatic marking for time, date, sample name
- ◆ Easy to operate

Applications

Automatic polarimeter is used in detection of sugar, pharmacy, food, drugs, chemical testing also for detection of starch, agriculture products, amino acids & other materials.

Specifications

Model No.	LPMR-A30
Measurement mode	Four modes: optical rotation, specific rotation, concentration and international sugar content
Calibration mode	Automatic Calibration
Measuring Range	$\pm 89.99^{\circ}$, $\pm 259^{\circ}Z$
Minimum reading	0.001 ^o (optical rotation)
Accuracy	$\pm 0.01^{\circ}$ ($-45^{\circ} \leq$ optical rotation $\leq +45^{\circ}$)
Repeatability (standard deviations)	0.002 ^o (optical rotation)
Measurable sample min. transmittance	1%
Light source	LED
Working wavelength	589.3 nm
Test tube	One 200 mm & One 100 ml
Temperature control mode	Built-in semiconductor
Temperature control range	10 to 45 °C
Temperature control accuracy	$\pm 0.2^{\circ}C$
Display mode	7 inch TFT touch screen
Data storage capacity	1000 sets of data
Interface	USB, RS232
Power supply	250 W
Power	AC 220V \pm 10% 50 Hz
Dimension	820 × 420 × 440 mm
Net weight	28 kg
Gross weight	32 kg