

Penetrometer LMPT-A11



info@labtron.com

www.labtron.com

Penetrometer LMPT-A11

Penetrometer LMPT-All is a temperature controlled unit for determining penetration of pavement petroleum asphalt, modified asphalt, liquid petroleum asphalt and emulsified asphalt. It has digital meter display which shows penetration number of sample. Equipped with automatic temperature controller and high accuracy temperature sensor. Separate automatic controlled temperature water bath for penetration determination. It is ideally used for different types of asphalt, food industries, highway engineering, etc.

Features

- Digital meter display shows penetration number of the sample
- Stable and reliable measured data
- Automatic magnetic stirrer
- High temperature control precision
- High accuracy temperature sensor
- Adjustable needle holder
- Automatic controlled temperature water bath

Application

Widely used for determining needle penetration of pavement petroleum asphalt, modified asphalt, liquid petroleum asphalt and emulsified asphalt, also for solid particle, powder, colloid mixture, highway engineering and food materials such as glycine, cheese, butter, cream, leavening agents, etc.

Specifications

| Model No | LMPT-A11 |
|------------------------------|----------------------------|
| Measurement range | 0 to 600 penetration scale |
| Timing controller | 5 sec or 60 sec |
| Time accuracy | ± 0.1 seconds |
| Resolution | 0.01 mm |
| Penetration accuracy | ± 1 penetration |
| Temperature control accuracy | 25 °C ± 0.1 °C |
| Environment temperature | 15 °C to 35 °C |
| Weight of standard needle | 2.5 ± 0.05 g |
| Power consumption | 200 W |
| Power supply | AC 220 V ± 10 %, 50 Hz |
| Dimensions (W × L × H) | 650 × 500 × 850 mm |
| Weight | 30 kg |