



**TRANSPARENT THERMOSTATIC
WATER BATH**

LTWB-A1 SERIES

TRANSPARENT THERMOSTATIC WATER BATH LTWB-A1 SERIES

Transparent Thermostatic Water Bath LTWB-A10

Transparent Thermostatic Water Bath LTWB-A10 is designed with transparent acrylic sheet, allows user clear observation of the objects that are being heated. This 6 L capacity, and RT to 100°C temperature range water bath offers high precision intelligent temperature control, with high brightness and digital display.

Transparent Thermostatic Water Bath LTWB-A11

Transparent Thermostatic Water Bath LTWB-A11 is designed with transparent acrylic sheet, allows user clear observation of the objects that are being heated. This 8 L capacity, and RT to 100°C temperature range water bath offers high precision intelligent temperature control, with high brightness and digital display.

Transparent Thermostatic Water Bath LTWB-A12

Transparent Thermostatic Water Bath LTWB-A12 is designed with transparent acrylic sheet, allows user clear observation of the objects that are being heated. This 20 L capacity, and RT to 100°C temperature range water bath offers high precision intelligent temperature control, with high brightness and digital display.

FEATURES

- Digital LED display with high brightness
- Effective prevention of steam leakage
- Controlled high precision temperature
- Transparent acrylic sheet, can see objects that are heated inside
- Size of Tube tank; Height 20 mm, Diameter 12.5 mm

APPLICATION

Transparent Thermostatic Water Bath is use for experimental process in scientific research labs, hospitals, petroleum and electronic components for evaporation.

SPECIFICATION

| Model | LTWB-A10 | LTWB-A11 | LTWB-A12 |
|-------------------|--------------------------------------|--------------------|--------------------|
| Capacity | 6 L | 8 L | 20 L |
| Temp. Range | RT to 100°C | | |
| Temp. Fluctuation | 0.5°C | | |
| Temp. Accuracy | ≤ ± 1°C | | |
| Tube Rank | 1 pc, Height 20 mm, Diameter 12.5 mm | | |
| Consumption | 600 W | 1000 W | 1500 W |
| Display | LED | | |
| Internal size | 270 × 120 × 150 mm | 270 × 120 × 150 mm | 480 × 270 × 150 mm |
| Packing size | 410 × 275 × 310 mm | 470 × 315 × 310 mm | 680 × 375 × 310 mm |
| Power supply | AC 110/220 V ± 10 %, 50/60 Hz | | |
| Net Weight | 6 kg | 7.5 kg | 13 kg |
| Gross Weight | 6.8 kg | 8.5 kg | 15 kg |