

Vacuum concentrator centrifuge LVC-A1 series



www.labtron.com

info@labtron.com

Vacuum concentrator centrifuge LVC-A1 series

Vacuum concentrator centrifuge LVC-A1 series offers exquisite design, TFT, LCD touch screen display with intelligent micro-computer controlled system and user-friendly operation interface. Centrifugal force is used to carry out the concentration of samples, vacuum conditions for evaporating solvents from the sample. This series comes with 1350 rpm, 1500 rpm, 2000 rpm and temperature range from room temperature to 55-60°C for different applications.

Features:

- ☑ TFT true color LCD touch screen display
- ☑ Intelligent microprocessor controlled technology, easy and direct operation interface
- Aluminum alloy drying room with corrosion resistant coating
- Transparent cover to observe operation status
- ☑ 0 to 99 h 59 min Condensation capacity
- Maintenance free and non-contact drive and rotation system
- Can be used in combination with cold trap

Applications:

Vacuum Concentrator centrifuge is used across chemical, petrochemical, food, pharmaceutical industry for residual analysis of an extracts, and mixtures like methanol/water or any drug/ solvent etc.

Specifications:

| Model no. | LVC-A10 | LVC-A11 | LVC-A12 |
|-------------------|--------------------|---------------------|-------------------|
| Rotor capacity | 1.5 ml×62 | 10 ml×12 or 50 ml×6 | 250 ml×6 |
| Speed | 1350 rpm | 1500 rpm | 2000 rpm |
| Temperature range | Room temp. to 55°C | Room temp. to 60°C | Room temp to 60°C |
| Condensation rate | 0-99 h 59 min | | |
| Dimension(L*W*H) | 500×490×280 mm | | 600×540×360 mm |
| Optional | Vacuum pump | | |

Optional Rotor:

| Suitable Model no. | Rotor Capacity | |
|--------------------|----------------|--|
| LVC-A11 | 10 ml×12 | |
| | 50 ml×6 | |
| LVC-A12 | 250 ml×6 | |

Optional Adapter:

| Suitable Model no. | Adapter Capacity | |
|--------------------|------------------|--|
| LVC-A12 | 50 ml×6×2 | |
| | 20 ml×6×5 | |

Optional Accessories:-

- Vacuum Pump
- Cold trap

Cold Trap Details:-

The Evaporation rate is influenced by the energy that has been absorbed and the speed of the vacuum pump. A relatively large evaporation surface area of a sample, rather than sample capacity and quantity is the blockage that affect the efficiency of the vacuum pump. Therefore instead of using bigger vacuum pump, employ the cold trap. The application of the cold trap helps to condense vapors on the one hand and enhance then evaporation density of organic solutions for better condensation.



Specifications:

- Circulation: Hermetic circulation
- Temperature adjustment: ±1°C
- Temperature range: Room temperature to -40°C
- Compressor Refrigerant Gas: R404 a
- · Volume: 4 L
- TFFT true color LCD touch wide screen indicating temperature of cold trap

Vacuum Pump Details:-



Specifications:

• Rotary vacuum pump

• Pumping Speed: 60 L/ m

• Extreme pressure: 0.08 mPa

• Power: 160 W

• Voltage: 230 V/50 Hz